DKS 20-40 Dübelklemmschelle 30060

CE 10/2025

Anwendungsbereiche:

Für die einfache Verlegung von Mantelleitungen (Einzelleitungen und Leitungsbündel) z. B. Antennenleitungen, Telefonleitungen.

Installationsanleitung:

- Bohren eines Loches mit 6 mm Ø,
- Kabel mit DKS umfassen,
- DKS mit dem Dübelteil ins Bohrloch stecken.

Produktdetails:

Farbe	hellgrau
Inhalt Pkg./Karton	200 / 4.000
Spannbereich	20 - 40 mm

Montage- und Verarbeitungshinweise:

Das oder die Kabel mit der DKS umfassen und die DKS mit dem Dübelteil in ein 6 mm Bohrloch stecken. Bohren. Stecken. Fertig!

Produktvorteile/Eigenschaften:

Gute Spannmöglichkeit des Kabels mit der DKS. Im verlegten Zustand ist die Schlaufe der DKS kaum sichtbar.

Technische Daten:

Material	PP, UV-stabilisiert Temperaturbereich: -10 °C bis +85 °C silikonfrei Material geprüft nach OVE R14 (LSFOH)
Gewicht pro	1,20 g
Max. Belastung	Referenzwerte: DKS 3-13: 99,2 N Beton, 108,72 N Vollziegel
Bruchlast	Referenzwerte: DKS 3-13: 248,00 N Beton, 271,80 N Hohlziegel
GTIN (EAN)	9 008439 400607

Schnabl® time saving products

Nur das ORIGINAL ist genial

Made in Austria

Schnabl Stecktechnik GmbH, Bahnhofplatz 1, Postfach 63, 3100 St. Pölten, Austria
Telefon +43 2742 22167-0, office@schnabl.works, www.schnabl.works

DKS 20-40 Dowel clamp 30060

CE 10/2025

Areas of application:

For the single installation of casing pipes (single cable and cable bundles) such as antenna cables, telephone lines and flex s.

Installation Guide:

- Drill a 6mm Ø hole
- Wrap the DKS around the cable
- Insert the DKS into the drill hole

Product details:

Colour	light grey
Content pack/box	200 / 4.000
Clamping range	20 - 40 mm

Mounting and usage instructions:

Cover the cable(s) with the DKS and insert the DKS into a 6 mm drill hole. Drill. Fasten. Done!

Product benefits/properties:

Good cable tension options with the DKS. When laid, the strap is barely visible.

Technical data:

Material	PP, UV stabilised Temperature range: -10 °C up to +85 °C silicon-free Material tested according OVE R14 (LSFOH)
Weight per piece	1,20 g
Max. reccd. load	Reference value: DKS 3-13: 99.2 N concrete, 108.72 N solid brick
Breaking load	Reference value: DKS 3-13: 248.00 N (24.8 kg) concrete, 271.80 N (27 kg) hollow brick
GTIN (EAN)	9 008439 400607

Schnabl®
time saving products

Only the ORIGINAL is ingenious

Made in Austria

Schnabl Stecktechnik GmbH, Bahnhofplatz 1, po box 63, 3100 St. Pölten, Austria
Telephone +43 2742 22167-0, office@schnabl.works, www.schnabl.works